Serial No. 10/786,309

Amdt. dated August 22, 2007

Reply to Office Action of May 24, 2007

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A flexible cable, comprising:

a flexible cable main body having one end configured to connect to a first part

Docket No. IK-0062

and the other end configured to connect to a second part on a side opposite to the first part and

configured to transmit signals between the first and second parts, wherein at least one of the first

and second parts is movable; and

a folded portion formed by folding in the form of a portion of the cable main

body folded so that two opposing faces are in contact with each other, two strips of said cable

extending from the folded portion in the same direction initially, wherein movement of said at

least one movable part of the first and second part is configured to occur between a first

position and a second position whereby corresponding movement of said flexible cable main

body is configured to occur only to one side of the folded portion connected to the at least one

movable part.

2. (Original) The flexible cable as claimed in claim 1, further comprising a folded-

state maintaining device configured to maintain a folded state of the folded portion.

Serial No. **10/786,309** Amdt. dated <u>August 22, 2007</u>

Reply to Office Action of May 24, 2007

(Original) The flexible cable as claimed in claim 2, wherein the folded-state
maintaining device comprises an adhesive member configured to bond both faces of the folded
portion to each other.

4. (Original) The flexible cable as claimed in claim 2, wherein the folded-state maintaining device comprises a reinforcement folded-plate attached to at least one side of both sides of the folded portion.

- (Original) The flexible cable as claimed in claim 2, wherein the folded-state maintaining comprises a folding clip with an insertion slot into which the folded portion is inserted.
- 6. (Original) The flexible cable as claimed in claim 2, wherein the folded-state maintaining device comprises a tape configured to wrap both sides of the folded portion.
- 7. (Original) The flexible cable as claimed in claim 1, wherein the cable main body is divided into a straight portion and a curved portion with respect to the folded portion and the curved portion is relatively longer than the straight portion.

Reply to Office Action of May 24, 2007

8. (Currently Amended) A disk drive comprising the flexible cable of claim 1, wherein the a end of the folded portion of the flexible cable main body not connected to the at least one movable part is vertically aligned with the other part of the first and second part.

9. (Currently Amended) A flexible cable, comprising:

a first end configured to be connected to a first part and a second end configured to be connected to a second part, so as to transmit signals between the first and second parts, at least one of the first and second parts being movable; and

a folded portion formed by folding in the form of a portion of the flexible cable between the first and second ends folded so that two opposing faces are in contact with each other, wherein two strips of said cable extend from the folded portion in the same direction initially and the folded portion does not deviate from vertical alignment with the first part, and wherein said second end is vertically aligned with said second part.

10. (Previously Presented) A disk drive comprising the flexible cable of claim 9, wherein movement of said at least one movable part of the first and second parts is configured to reciprocally occur along a prescribed range between a first position and a second position whereby corresponding movement of a main body of said flexible cable is configured to occur only to one side of the folded portion connected to the at least one movable part.

Reply to Office Action of May 24, 2007

11. (Currently Amended) A flexible cable, comprising:

a first end configured to be connected to a first part and a second end configured

to be connected to a second part so as to transmit signals between the first and second parts, at

least one of the first and second parts being movable; and

a folded portion formed by folding in the form of a portion of the flexible cable

between the first and second ends folded so that two opposing faces are in contact with each

other, two strips of cable extending from the folded portion in the same direction initially, a first

said strip extending into a straight portion having the first end of the flexible cable and a second

said strip extending into a curved portion having the second end of the flexible cable being

formed by the folding portion of the flexible cable, wherein a vertex of the curved portion does

not deviate from vertical alignment with the second end prior to movement of the first end.

12. (Previously Presented) A disk drive comprising the flexible cable of claim 11,

wherein the flexible cable is configured to be directly connected to an optical pickup of a disk

drive.

13. (Currently Amended) A disk drive, comprising:

a main base;

Docket No. IK-0062

Serial No. 10/786,309

Amdt. dated August 22, 2007

Reply to Office Action of May 24, 2007

a pickup base installed on the main base and provided with parts for recording

and reproducing signals on and from a disk, including an optical pickup linearly movable within

a predetermined region;

a board fixedly installed on a side of the main base and configured to control

driving of the parts including the optical pickup; and

a flexible cable having a folded portion formed by folding in the form of a portion

of a flexible cable main body folded so that two opposing faces are in contact with each other,

wherein two strips of cable extend from the folded portion in the same direction and are

connected, respectively, directly to the optical pickup and to the board so as to transmit signals

therebetween.

14. (Previously Presented) The disk drive as claimed in claim 13, further comprising:

a tray configured to move inside and outside the main base so as to move the disk

between a loading position and an unloading position.

15. (Previously Presented) The disk drive as claimed in claim 13, wherein the cable

main body is divided into a straight portion and a curved portion with respect to the folded

portion.

Docket No. IK-0062

Serial No. 10/786,309 Amdt. dated August 22, 2007

Reply to Office Action of May 24, 2007

16. (Currently Amended) The disk drive claimed in claim 15, wherein the folded

portion is formed near-adjacent one of the optical pickup and the board.

17 Canceled

(Original) The disk drive as claimed in claim 13, further comprising a folded-state 18.

maintaining device configured to maintain a folded state of the cable main body.

(Previously Presented) The disk drive as claimed in claim 18, wherein the folded-19.

state maintaining device comprises an adhesive member configured to bond both faces of the

folded portion to each other.

(Previously Presented) The disk drive as claimed in claim 18, wherein the folded-20.

state maintaining device comprises a reinforcement folded-plate attached to at least one side of

both sides of the folded portion.

21. (Previously Presented) The disk drive as claimed in claim 18, wherein the folded-

state maintaining comprises a folding clip with an insertion slot into which the folded portion is

inserted.

Serial No. 10/786,309

Amdt. dated August 22, 2007

Reply to Office Action of May 24, 2007

22. (Previously Presented) The disk drive as claimed in claim 18, wherein the folded-

Docket No. IK-0062

state maintaining device comprises a tape configured to wrap both sides of the folded portion.

23. (Previously Presented) The disk drive of claim 13, wherein movement of the

optical pickup is configured to be between an inner end and an outer end of said predetermined

region, wherein corresponding movement of said flexible cable main body is configured to occur

only to one side of a position of the folded portion when said optical pickup is at said outer end.

24. (Previously Presented) The disk drive of claim 23, wherein said folded portion

and said two strips of cable are vertically aligned.

25. (Previously Presented) The disk drive of claim 24, wherein said folded portion

and said two strips of cable are vertically aligned throughout their respective entire lengths.